

PART NUMBER - VALVE SELECTION

Series	Size	-	Base Code	Body	Ball/ Stem	Seats	Seals	-	Service Mod	Ball Mod	Special Features
14	0200	-	11001	S	S	R	R	-	N	N	
1	2	-	3	4	5	6	7	-	8	9	-10

Example: 140200-11001SSRR-NN = 2" 7000 with SW (Socketweld Ends), Stainless Steel Body, Stainless Steel Ball and Stem, RPTFE Seats, RPTFE Seals

1	Series	14	3 Piece Valves	7000 Model 8000 Model	Website Link	Brochure	DM7000 DM8000	Website Link	Brochure
---	--------	----	----------------	--------------------------	------------------------------	--------------------------	------------------	------------------------------	--------------------------

2	Size*	0025	1/4"	0100	1"	0250	2-1/2"
		0038	3/8"				
		0050	1/2"				
		0075	3/4"				

-	-
---	---

3	Base Code (Model)	11000	Model 7000/8000 w/ NPT Ends	110M0	Model DM7000/DM8000 w/ NPT Ends
		11001	Model 7000/8000 w/ SW Ends	110M1	Model DM7000/DM8000 w/ SW Ends
		11002	Model 7000/8000 w/ BW Ends	110M2	Model DM7000/DM8000 w/ BW Ends (Sch40)
		11023	Model 7000/8000 w/ Extended SW Ends	110M3	Model DM7000/DM8000 w/ Ext SW Ends
		11024	Model 7000/8000 w/ Extended BW Ends (Sch40)	110M4	Model DM7000/DM8000 w/ Ext BW Ends (Sch40)
		11013	Model 7000/8000 w/ NPT x SW Ends	110M7	Model DM7000/DM8000 w/ ANSI 150 Flanged Ends
		11017	Model 7000/8000 w/ ANSI 150 Flanged Ends	11F00	Model 7000 w/ NPT Ends (NSF 61)

4	Body	S C	316 Stainless Steel (7000 & DM7000) WCB Carbon Steel (8000 and DM8000)	A	Alloy 20
---	------	--------	---	---	----------

5	Ball & Stem	S	316 Stainless Steel Ball with 316 Stainless Steel Stem	A	Alloy 20 Ball and Alloy 20 Stem
---	-------------	---	--	---	---------------------------------

6	Seats	R	RPTFE	U T F	UHMWPE PTFE PTFE (NSF 61 Registered)
		J	TFM 1600		
		K	Tek-Fil		

7	Seals	R	RPTFE	U T	UHMWPE PTFE
		J	TFM 1600		
		F	PTFE (NSF 61 Registered)		

-	-
---	---

8	Service Modification	N	None	X F	Oxygen Cleaning NSF 61 Certification and Tagging
		C	General Cleaning		

9	Ball Modification	N	None
		H	Vented Ball

-	-
---	---

10	Special Features (Optional)	0001	Cavity Fillers	0031 0210	Polished 10-15 Ra Polished 8-12 Ra	0055 ????	Special Trust Washer Material Consult Factory
		0009	Polished to 30-35 Ra Polished				
		0032	Polished to 20-25 Ra				

NOTES:

7000 & 8000 Model Valves come standard with a Lockable Lever. DM7000 & DM8000 come bare stem.

*Direct Mount Valves (DM7000/DM8000) are only Available in 1/2" - 2" Size Range. See Price Pages for sizes and End Connections Special End Connections like other Schedule BW end caps are available on request - Consult Factory

Not all End Connections are available in all sizes - See price pages

General Cleaning per Flow-Tek WI-125 (solvent method) & Bagged meets ASME BPE-2002A Stainless Steel Welded Ends are made of 316L - ASTM A351 Gr CF3M

Special Materials of Construction are available on request.